

GIANT FULL E 1 PRO 2018
Sur demande taille small
medium et large
valeur 4700€
vendu -25% 3500€



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Black/Yellow/Red
CADRE	ALUXX-SL Grade Aluminum
FOURCHE	Fox 34 Float Performance 27.5+ 140mm, EVOL, 3-position Grip Damper, tapered steerer, 'Boost' 110x15QR, e-Bike optimized
AMORTISSEUR	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position lever, 185x52.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Connect TR 780x31,8mm
POTENCE	Giant Connect [50 S, 60 ML, 70XL]
TIGE DE SELLE	Giant Contact Switch, remote height adjust [100 S/M, 125 L, 150 XL]
SELLE	Giant Contact neutral
PÉDALES	Giant Original MTB-Sport, Aluminium Platform, CrMo, replaceable pins
DÉRAILLEUR	
MANETTES	Shimano SLX 2x11sp
DÉRAILLEUR AVANT	Shimano XT direct mount
DÉRAILLEUR ARRIÈRE	Shimano XT Shadow+, 11sp
FREINS	Shimano BR-M6000 200/200mm Disc
LEVIERS DE FREIN	Shimano BL-M6000 i-spec II
CASSETTE	SunRace CS-MS8 11-40T, 11sp
CHAÎNE	KMC X.11e EcoProteQ, e-bike optimized
PÉDALIER	Custom forged crankset by FSA, 28/38T, Boost 2x spider
ROUES	
JANTES	Giant GE35, Tubeless ready, 27.5" 35mm aluminum, e-bike optimized
MOYEURS	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
RAYONS	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
PNEUS	Maxxis Rekon 27.5x2.6" foldable, EXO protect, Dual Compound [R], 3C Maxx Grip [F], Tubeless
EXTRAS	Giant EnergyPak 4A fast charger
TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Pro
CAPTEURS	Giant PedalPlus 4-sensor technology
COMPTEUR LCD	Giant RideControl EVO, grip launch control with walk assist, mini USB charger
BATTERIE	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion

CARACTÉRISTIQUES

- Giant SyncDrive Pro central motor, performance tuned
- Giant EnergyPak500 lithium-ion battery for longest range
- Fox 34 Performance 140mm travel fork
- Shimano XT/SLX 2x11-speed Drivetrain
- Contact Switch remote height adjust seatpost
- Shimano hydraulic brakes
- Color: Black/Yellow/Red



GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	431	450	500	530
Angle de tube de selle	73,0°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	565	590	610	635
Longueur du tube de direction (mm)	125	125	140	160
Angle du tube de direction	67,0°	67,0°	67,0°	67,0°
Déport de fourche (mm)	42	42	42	42
Sentier (mm)	109	109	109	109
Empattement (mm)	1143	1168	1190	1217
Longueur fourche de pédalier (mm)	463	463	463	463
Hauteur du boîtier de pédalier (mm)	12,0	12,0	12,0	12,0
Stack (mm)	610	610	624	642
Reach (mm)	378	403	419	438
Hauteur en statique (mm)	768	769	806	832
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	50	60	60	70
Longueur des manivelles (mm)	170,0	170,0	170,0	170,0
Diamètre des roues	27.5+	27.5+	27.5+	27.5+

Produits conformes aux exigences de sécurité (décret n°95-937). GIANT France se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles. Les prix sont librement fixés par les revendeurs Giant de ce fait ils n'apparaissent pas sur le site Internet.